



Wall-hung electric storage water heater



GUARANTEE OF QUALITY



POLYURETHANE INSULATION



ENAMELLED STEEL TANK

- EXCLUSIVE DESIGN
- HIGH QUANTITY OF HOT WATER MIXED
- NEW STRONG THERMOMETER
- THERMOSTAT WITH BIPOLAR SAFETY DEVICE
- OVERSIZE MAGNESIUM ANODE
- HIGH EFFICIENCY WITH EXPANDED POLYURETHANE INSULATION
- PRESSURE SAFETY VALVE TESTED AT 8 BAR
- PRODUCT TESTED TO THE HIGHEST QUALITY STANDARDS
- GLASSLINED INNER TANK TESTED AT 16 BAR



ease
guaranteed

Technical data - Overall dimensions

	PRO R		PRO R		
	120 v 1,8 PL	150 V 1,8K PL	120V	150V	
Capacity	l	120		150	
Installation		V		V	
TD/TS		-		-	
Size		Regular		Regular	
Power	kW	1,8		1,8	
Voltage	V	230		230	
Heating time ($\Delta T=45^{\circ}\text{C}$)	h,min	3:40'		4:35'	
Heat dispersion at 65°C	kWh/24h	1,6		1,6	
Max working pressure	bar	8		8	
Max working temperature	$^{\circ}\text{C}$	75		75	
Weight	kg	35		42	
Class	IP	IPX 3		IPX3	
			a mm	1108	1335
			b mm	953	980

PRO R 120 V 1,8K PL
3700227

PRO R 150V 1,8K PL
3700257



LEGEND

E Cold water inlet G 1/2"

U Hot water outlet G 1/2"